

MEDIAPLAY DSI722AJS

Satellite HD Receiver



SATELLITE

VIDEO

The MediaPlay DSI722AJS is a state-of-the-art decoder allowing access to premium belN sport content in a fully secured and reliable design from the global leader in satellite set top boxes.

Access to belN sport content

Secure and exclusive access to belN sport network through new satellite receiver incorporating 1080i/60 HD Decode

Unique belN Sport Design

Unique look and feel building upon Technicolor's expertise in Industrial design

Cisco Middleware and Conditional Access solution

Pre-integrated with Cisco VideoGuard SmartCard security

Advanced Video Services

Including: Favorite channels, Electronic Program Guide, Channel mosaic.

Features at a Glance

- Unique belN Sport design and content
- HD 1080i/60 Decode capability
- DVB-S2 tuner
- Wide range power supply



MEDIAPLAY DSI722AJS

Satellite HD Receiver

Technical Specifications

DVB-S2 Interface

■ Modulation	QPSK & 8PSK
■ LNB power capability	350mA
■ LNB Control Capability	DiSEqC 1.0, upgradable in 1.2
■ Symbol Rates	2-45 MBaud
■ Digital Input frequency range	950 - 2150 MHz

MPEG Video Decoder

■ Standard	MPEG-4 H264/AVC, MPEG-2, Decode up to 1080i/60
■ Aspect ratio	4:3, 16:9, Pan & Scan, letterbox
■ Video Scaling	Variable

OSD

- Advanced user interface

MPEG Audio Decoder

■ Standard formats	MPEG1 Layers I & II (Mono, Dual Channel, Joint Stereo, Stereo) MPEG2 Layer II backward compatible modes, Mp3, Dolby Digital Plus, AAC
--------------------	--

System Resources

■ Processor	Broadcom 7358
■ RAM	256MB DDR3
■ Flash Memory	4MB NOR plus 128MB NAND

Software

■ Middleware Solutions	Middleware Solution Cisco MediaHighway
■ CAS	Cisco VideoGuard SmartCard

Front Panel

- 2 LEDs
- 1 key

Side Panel

- Smart card slot on side

Rear Panel

■ Satellite Input	1 x F type
■ Analog Audio	Twin RCA Stereo audio outputs (left and right)
■ Composite video output	1 x RCA Connector
■ Digital Audio	Yes (Optical)
■ HDMI	Yes
■ Power connector	

RCU Protocols

- RC5 with 36kHz IR modulation

General Data

■ Dimensions mm approx.	180x160x40
■ Power supply	12V External PSU
■ Input voltage	100-240V - 50/60Hz
■ Operating temperature range	5-45°C

Logistic Data

Container	20»	40»	80»
DSI722AJS	4360 units	8720 units	17440 units



TECHNICOLOR WORLDWIDE HEADQUARTERS
1, rue Jeanne d'Arc
92443 Issy-les-Moulineaux France
Tel.: 33 (0) 1 41 86 50 00 - Fax: 33 (0) 1 41 86 58 59

www.technicolor.com

SALES CONTACT

For more information please get in touch with your usual sales representative or use the following email:

MEASalescontact@technicolor.com



© Copyright 2013 Technicolor. All rights reserved. Photos and specifications are subject to change. Availability of specific functions may be network and operator dependent. All trade names referenced are trademarks of their respective companies. DS-276-v0.1-1310